

Features

- Precise & User Friendly
- Precise PWM based DC Stepper motor Drive
- Occlusion adjustable Spring loaded Pump Head
- Advanced EEPROM technology for data storage
- Membrane keypad with Menu driven LCD
- Complied with CE requirement
- Pumps are available with RS 232 / RS 485 interface




Specification

No. of Channels	One
Flow Rate	0.1 to 499.9 ml/min
Set Volume	0 to 999.9 ml
Interval Time	0 to 99.9 sec.
Tubing	1 to 5 mm ID, 1 to 1.6 mm Wall thickness
No. of Rollers	2
Pressure	UP to 2 Bar
Accuracy	± 1 %
Input Supply	230V +/- 10%, 50Hz, Single phase AC, 60 Watt
Display	Single line 8 Character Liquid crystal Display
Motor	DC Stepper Motor (Cont. Duty)
Drive	Microcontroller Based control Circuit and PWM Based DC Stepper Motor Drive
Remote ON	Potential free Digital Input
Weight	8 Kgs (Approx.)

Material of construction

Enclosure	Powder coated Aluminium
Outer ARM	Anodized Aluminium
ARM Cover	Transparent Polycarbonate
Rotor	S.S.316/S.S.304
Rollers	Carbon Filled Nylon

Dimension



Contact US

RAVEL HITEKS PVT LTD.,
150A, Electronics Industrial Estate, Perungudi,
Chennai-600 096. India.
Ph:044-2496 3241 / 3251 / 1004 / 0825,
Fax : 91-44-4204 9599
Email:sales@ravelhiteks.com
Web: www.ravelhiteks.com

