

Features

- Accurate & User Friendly
- Self Priming
- Rugged Variable Frequency Drive
- Membrane keypad with LED Display
- Occlusion adjustable Spring loaded Pump Head
- Complied with CE requirement




Specification

No. of Channels	One
Flow Rate	1 to 50 Ltr/min
Speed	20 to 200 RPM
Tubing	10 to 25 mm ID, 3 to 4 mm Wall thickness
No. of Rollers	2
Pressure	UP to 2 Bar
Accuracy	± 2 %
Input Supply	230V +/- 10%, 50Hz, Single phase AC, 750 Watt
Display	Four digit LED seven segment Display
Motor	3 φ AC Geared Motor (Cont. Duty)
Drive	Single Phase Input, three phase Output Variable Frequency Drive
Mode Of Operation	Auto / Manual
External Speed control	4...20mA signal
Weight	40 Kgs (Approx.)

Material of construction

Enclosure	Powder coated Aluminium
Outer ARM	Anodized Aluminium
ARM Cover	Transparent Polycarbonate
Rotor	S.S.316/S.S.304
Rollers	Carbon Filled Nylon

Dimension



Contact US

RAVEL HITEKS PVT LTD.,
150A, Electronics Industrial Estate, Perungudi,
Chennai-600 096. India.
Ph:044-2496 3241 / 3251 / 1004 / 0825,
Fax : 91-44-4204 9599
Email:sales@ravelhiteks.com
Web: www.ravelhiteks.com

